HD 720p Real Time Network Cube Camera

YUC-HS85

Feature

Ultra compact size & easy operation
H. 264/ MPEG-4/ JPEG triple codec
2-way audio support for easiest communication
Micro SD card for sudden network outage or alram recording
DI/DO for external alarm application
Mobile surveillance
PoE/ Wireless support
ONVIF compliant



HS85

		HS85
Camera Features	Image Pick-up Device	1/4"Progressive Scan CMOS sensor
	Effective Pixels (H x V)	1280x720
	Min Illum	0.5Lux
	Lens Type	Fixed Lens
	Focal Length/ F-number	f: 4.2mm , F: 1.6
	Electronic Shutter Speed	1/5~1/100,000 second(s), indoor, outdoor setting
	Gain Control	AGC Adjustable (2x~24x)
	Gamma	Indoor & Outdoor
Image	Network Compression	H.264/ MPEG-4/ M-JPEG
	Image Size	1280x800, 1280x720, 640x480, 320x240,176x144
	Max. Frame Rate	30fps in all resolutions
	Intelligence Support	D-WDR,DNR,Sense-Up, Motion Dectecion, Mask, VBR/CBR
Network Server	Protocols	Access list, Bonjour, DHCP, DDNS, FTP, HTTP, HTTPS, IPv4, IPv6, IEEE 802.1X Multicast NTP PPPoE, QoS/DSCP, RTSP, SAMBA, SMTP, SNMP UPnP, UPnP Forwarding
	Traffic Controls	32/48/64/96/128/196/256/320/384/448/512/576/640/704/768Kbps 1/1.5/2/2.5/3/3.5/4/6/8Mbps
	Number of Users	Max. 10 connections for singal video
	Safety	User-ID and password
Audio	Audio Communication	2-way-halfduplex
	Audio Compression	G.711(64Kbps)/ G.726(24Kbps/ 32Kbps)
	Frequency	300 Hz - 3.4KHz
	Audio In	Built-in Mic, Support 2-way audio
	Audio Out	3.5mm, line out for external speaker
Interface	Ethernet	RJ45 (10/ 100 Base-T)
	Wireless	802.11b/g/n
	Sensor I/O	DI/DO
	Storage Device	Micro SD, FTP, Mail, NAS, and SAMBA
General	Processors	ARM 9 ,32 bit RISC
	Memory	128MB-RAM, 16MB-Flash
	Power	PoE IEEE 802.3 af (Class 0)
	Operation Voltage	DC12V
	Dimen./Weight	93.7(H)x59(W)x45.5(D)mm 80g / 12pcs per carton
	Operation Temp.	-10°C ~ +45°C, relative moisture 20%-90%
	Included Accessories	CD/ IP recorder/ IP installer/ Installation guide/ Detail user manual/Bracket

Product code: P-PoE, W-WiFi



